



## Software Function

- Support GSM900 / DCS1800 dual-band or GSM850 / DCS1900 dual-band, automatic exchange, GPRS is optional;
- Voice features MO-call and MT-call;
- Redial; Talk-time Display;
- Talking operation (mute, volume adjustment, DTMF);
- Speed dial; Emergency call;
- Caller ID; Support SIM message management;
- Short Message function Send and receive short message;
- Broadcast message;
- Short message edit, read, send, forward and reply;
- Can store 200 short messages;
- SIM card short message management;
- Talk Record The phone can store 10 groups of missed call, received call and dialed call; Call statistic;
- Phonebook The phone can store 100 phone numbers; SIM card phonebook management function;
- Sound 20 ring tones; Key sound; Many prompt-tones;
- Clock Real-time clock; 4 independent alarm clocks;
- Display Large LCD (128x64 Pixel); Display contrast adjustable;
- Power indication; Power management;

## Management Function

- Security Lock card; Lock phone; Lock network;
- Lock long distance call;
- Lock cell-up to 20 entries;
- Lock LAC-up to 20 entries;
- Dial operation Forbid number-up to 100 entries;
- Auto-plus local area code, auto-plus IP connection number;
- Local number management, up to 500 entries;
- Phone hidden code management;
- Short message remote management;

## Specification

- Mechanical Size Dimension: 220mm x 204mm x 79mm
- Weight: 800g
- Electric Performance Power: Power adapter and Ni-H battery
- Power consumption: standby $\leq$ 0.3W;talking $\leq$ 35W
- Environmental Requirement
- Working temperature -10 $^{\circ}$ C ~ 50 $^{\circ}$ C
- Relative Humidity 10% ~ 95%
- Atmospheric pressure 86kPa ~ 106kPa
- Environmental noise <60db
- Switch power adapter, AC 220V input, DC 7V output
- High performance chargeable battery, standby for 72 hours and call for three hours